

## Model: KL1200A

Powered by KUBOTA



Maximum Height

**9**  
Meters

Total Lumens

**33000**  
LM/LIGHT

Light coverage

**4000**  
m<sup>2</sup>

LED

**4\*300**  
Watt

Lifting System

**A**  
Auto

RPM

**1500/1800**



Light tower	
Tower Model	KL1200A
Max. height	9M
Lamps	LED
Mast	electrical winch, 6 sections
NO. of Lamps	4*300W
Total lumens	33000 LM/LIGHT


Performance Data	
Rated frequency (HZ)	50/60
Voltage	230/240-120VAC
Fuel capacity	76L
Aprox. Run time	59 hours
Gross weight	810 Kg

Engine	
Engine model	Z482
Speed (rpm)	1500/1800RPM
Cylinder	2L
Aspiration	Naturally aspirated
Cooling system	Liquid coolant
speed governor	Mechanical

Light tower	
Rotation angle	330°
Light's fixture	Square
Auxiliary sockets	1
Axle with brakes	single axle without brake
NO. of stabilizing legs	4
Wheels	2*14" rim
Towing connection	2" ball
Max. towing speed	80km/h
Max. against wind	17.5m/s
Acoustic pressure@7m	72db

Alternator	
Alternator model	LT3N-75/4
insulation	H
alternator protection grade	IP23

Dimension: L x W x H	
KL1200A	2300mm * 1320mm * 2900mm



## Model: KL1200H

Powered by KUBOTA



Maximum Height

**9**  
Meters

Total Lumens

**33000**  
LM/LIGHT

Light coverage

**4000**  
m<sup>2</sup>

LED

**4\*300**  
Watt

Lifting System

Hydraulic

RPM

**1500/1800**



Light tower	
Tower Model	KL1200H
Max. height	9M
Lamps	LED
Mast	Hydraulic, vertical 7 sections
NO. of Lamps	4*300W
Total lumens	33000 LM/LIGHT


Performance Data	
Rated frequency (HZ)	50/60
Voltage	230/240-120VAC
Fuel capacity	120L
Aprox. Run time	56 hours
Gross weight	1360 Kg

Engine	
Engine model	Z482
Speed (rpm)	1500/1800RPM
Cylinder	2L
Aspiration	Naturally aspirated
Cooling system	Liquid coolant
speed governor	Mechanical

Light tower	
Rotation angle	330°
Light's fixture	Square
Auxiliary sockets	1
Axle with brakes	single axle without brake
NO. of stabilizing legs	4
Wheels	2*14" rim
Towing connection	ring / 50mm ball
Max. towing speed	80km/h
Max. against wind	20m/s
Acoustic pressure@7m	72db

Alternator	
Alternator model	LT3N-75/4
insulation	H
alternator protection grade	IP23

Dimension: L x W x H	
KL1200H	3420mm * 2800mm * 2460mm



## Model: KL1200M

Powered by KUBOTA



Maximum Height

9 Meters

Total Lumens

33000 LM/LIGHT

Light coverage

4000 m<sup>2</sup>

LED

4\*300 Watt

Lifting System

Manual

RPM

1500/1800



### Light tower

Tower Model	KL1200M
Max. height	9M
Lamps	LED
Mast	Manual horizontal, 3 section
NO. of Lamps	4*300W
Total lumens	33000 LM/LIGHT

### Performance Data

Rated frequency (HZ)	50/60
Voltage	230/240-120VAC
Fuel capacity	170L
Aprox. Run time	360 hours
Gross weight	910 Kg

### Engine

Engine model	Z482
Speed (rpm)	1500/1800RPM
Cylinder	2L
Aspiration	Naturally aspirated
Cooling system	Liquid coolant
speed governor	Mechanical

### Light tower


Rotation angle	330°
Light's fixture	Square
Auxiliary sockets	2
Axle with brakes	single axle without brake
NO. of stabilizing legs	4
Wheels	2*14" rim
Towing connection	ring / 50mm ball
Max. towing speed	80km/h
Max. against wind	20m/s
Acoustic pressure@7m	72db

### Alternator

Alternator model	LT3N-75/4
insulation	H
alternator protection grade	IP23

### Dimension: L x W x H

KL1200M	4360mm * 1430mm * 1450mm
---------	--------------------------



## Model: **KDJ4000M**

Powered by KHOLER



Maximum Height  
7 Meters

Total Lumens  
110000 LM/LIGHT

Light coverage  
5000 m<sup>2</sup>

Metal Halid  
4 \* 1000 Watt

Lifting System  
Manual

RPM  
3000/3600



### Light tower

Tower Model	KDJ4000M
Max. height	7M
Lamps	Metal Halid
Mast	Manual vertical, 5 section
NO. of Lamps	4 * 1000W
Total lumens	110000 LM/LIGHT

### Performance Data

Rated frequency (HZ)	50/60
Voltage	230/240-120VAC
Fuel capacity	38L
Aprox. Run time	25 hours
Gross weight	500 Kg

### Engine

Engine model	KD440
Speed (rpm)	3000/3600RPM
Cylinder	1L
Aspiration	Naturally aspirated
Cooling system	Air-cooled
speed governor	Mechanical

### Light tower


Rotation angle	Not available
Light's fixture	Rectangle
Auxiliary sockets	NO
Axle with brakes	single axle without brake
NO. of stabilizing legs	2
Wheels	2 * 13" rim
Towing connection	2" ball
Max. towing speed	80km/h
Max. against wind	14m/s
Acoustic pressure@7m	77db

### Alternator

Alternator model	REQ
insulation	H
alternator protection grade	IP23

### Dimension: L x W x H

KDJ4000M	2260mm * 1050mm * 2700mm
----------	--------------------------



Distributed by

## Model: KJ4000A

Powered by KUBOTA



Maximum Height

**9**  
Meters

Total Lumens

**110000**  
LM/LIGHT

Light coverage

**5000**  
m<sup>2</sup>

Metal Halid

**4 \* 1000**  
Watt

Lifting System

**A**  
Auto

RPM

**1500/1800**



Light tower	
Tower Model	KJ4000A
Max. height	9M
Lamps	Metal Halid
Mast	electrical winch, 6 sections
NO. of Lamps	4 * 1000W
Total lumens	110000 LM/LIGHT


Performance Data	
Rated frequency (HZ)	50/60
Voltage	230/240-120VAC
Fuel capacity	100L
Aprox. Run time	28 hours
Gross weight	850 Kg

Engine	
Engine model	D1105-BG
Speed (rpm)	1500/1800RPM
Cylinder	3L
Aspiration	Naturally aspirated
Cooling system	Liquid coolant
speed governor	Mechanical

Light tower	
Rotation angle	330°
Light's fixture	Oval
Auxiliary sockets	1
Axle with brakes	single axle without brake
NO. of stabilizing legs	4
Wheels	2 * 14" rim
Towing connection	2" ball
Max. towing speed	80km/h
Max. against wind	17.5m/s
Acoustic pressure@7m	72db

Alternator	
Alternator model	LT3N-130/4
insulation	H
alternator protection grade	IP23

Dimension: L x W x H	
KJ4000A	2420mm * 1360mm * 3050mm



## Model: KJ4000H

Powered by KUBOTA



Maximum Height

9 Meters

Total Lumens

110000 LM/LIGHT

Light coverage

5000 m<sup>2</sup>

Metal Halid

4 \* 1000 Watt

Lifting System

Hydraulic

RPM

1500/1800



Light tower	
Tower Model	KJ4000H
Max. height	9M
Lamps	Metal Halid
Mast	Hydraulic, vertival7 sections
NO. of Lamps	4 * 1000W
Total lumens	1 10000 LM/LIGHT


Performance Data	
Rated frequency (HZ)	50/60
Voltage	230/240-120VAC
Fuel capacity	120L
Aprox. Run time	84 hours
Gross weight	1410 Kg

Engine	
Engine model	D1105-BG
Speed (rpm)	1500/1800RPM
Cylinder	3L
Aspiration	Naturally aspirated
Cooling system	Liquid coolant
speed governor	Mechanical

Light tower	
Rotation angle	330°
Light's fixture	Rectangle
Auxiliary sockets	1
Axle with brakes	single axle without brake
NO. of stabilizing legs	4
Wheels	2 * 16" rim
Towing connection	ring / 50mm ball
Max. towing speed	80km/h
Max. against wind	20m/s
Acoustic pressure@7m	72db

Alternator	
Alternator model	LT3N-130/4
insulation	H
alternator protection grade	IP23

Dimension: L x W x H	
KJ4000H	3420mm * 2800mm * 2460mm



Distributed by